

Electrical System with large 480V VFD, Amp-Trap Filter, and Isolation Transformer. Installed VSGR. The results are:


Removed Isolation Transformer.




Power Quality Testing on the Line 15 Extruder Machine Power Feed Phase Angle Shift of 6° from nominal and a Phase Voltage Imbalance over 5%



Phase Angle Corrected and Phase Voltages Balanced With Phaseback ON




Third Harmonic 38% with Phaseback OFF




HARMONICS TREND H3 %f U 5.2% 39.5 Ō 0:01:10 -0-0.0 B 39.5 0.0 39.5 0.0 141.0 d 5 3m 2770 60Hz 30 WYE 2,m 1,m 09/02/11 10:40:28 DEFAULT Z00M (\$) CURSOR ON OFF METER RUN


Phase Voltage Notching Causing Waveform Distortion with Phaseback OFF




Phase Voltage Waveform Distortion Reduced with Phaseback ON



Phase Voltage Imbalance with Phaseback OFF



Phase Voltages Balanced with Phaseback ON





Cy Cates


cycates@cycates.com

832 647 4606


www.cycates.com







The harmonics Solution can be switched ON or OFF as Phaseback is in the circuit.



| POWER A 0.39 | & ENERGY T | | DPF | F T 0.41 DP | F |
|-----------------|-------------------|------------|---------------------|------------------|---|
| 0.55 | FUND | ٢ | 0:02:07 | 9 | - |
| 0.30 0.55 | | | | | • |
| 0.30 0.55 | | | ····· | | • |
| 0.30 0.44 | | | | | |
| 0.40 | 4m 11 10:52:39 | 3m 2770 | 2m J 60Hz 3.0 WY | 1m 'E DEFAULT | |
| PREU. NEXT | CURSO | | OM ↔ ME | TER HOLD | |